

ESP726 Continuous Forms Cutter



DOCUMENT PROCESSING SOLUTIONS



ENERGY SAVING PRODUCTS

713 George Washington Turnpike

Burlington, CT 06013-2037

Phone (860) 675-6443 Fax (860) 675-1579

www.espcorp.com sales@espcorp.com



ESP726 Continuous Forms Cutter

Designed to meet the demands of high-volume form processing. Utilizing an advanced microprocessor controller, the ESP726 can store up to 41 different job settings, including single-cut, strip-cut, and multiple length cuts. These features, coupled with the ESP726's rugged design, will give years of reliable and trouble-free usage.

Features/Benefits

Advanced Microprocessor Controller enables advanced programmability and easy future upgrades.

LCD Display and 8 Button Control Panel displays current status and all job setup parameters.

Forms Depth: 1/6" and 1/8" allows greater flexibility of form size specifications.

Auto Paper Advance for quick, hands-free paper loading.

Paper End Sensor for automatic paper-end shutdown.

Central Width Adjustment allows quick and accurate width changes to accommodate many form sizes.

Stores up to 41 Different Jobs to reduce setup time = increased production.

Ultrasonic Loop Control automatically monitors and adjusts to printer speed.

Printer Interface Included; should an error occur, the ESP765 will notify the printer and stop production.

Wheel Mounting allows easy movement from one area to another.

Optional Descending Stacker with 3,000 sheet capacity.

Optional Four-foot Output Conveyor for continuous uninterrupted forms delivery.

Optional Slitter/Merger Unit allows wide web forms to be cut and output in a single stream.

Works with Optional Folder, giving you a total solution for a finished product online with a printer.

Specifications

MACHINE

Height	46"
Width	37 ¹ / ₂ "
Length	44 ¹ / ₂ "
Weight	435 lb.
Electrical	1.5 KVA 120V 50/60HZ*

APPLICATION

Feed Pitch	1/6" or 1/8"
Performance	4" - 34,500 cuts/hr. 8" - 24,800 cuts/hr. 12" - 19,300 cuts/hr.

FORMS

Height	Min.	2 ¹ / ₂ "	Max.	30"
Width	Min.	3 ¹ / ₂ "	Max.	20"
Weight	Min.	53g/m ²	Max.	200g/m ²

OPTIONS

* International Power Option
Center Slitter (up to 4)
ESP706 Forms Conveyor
ESP746 Slitter/Merger
ESP750 Descending Stacker
ESP755 North-South Job Separator
OMR - Optical Mark Recognition
Conveyor Stacker
Double Blade 1/6" Trim
Trim Choppers

The ESP726 is certified to American, Canadian, and European safety standards:

